



Safety Data Sheet

Page 1 of 11

LOCTITE SF 7900 AE 400ML

SDS No. : 326229

V001.4

Date of issue: 24.03.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE SF 7900 AE 400ML

Intended use: Coating

Supplier:
Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

E-mail address of person responsible for Safety Data Sheet: SDSinfo.Adhesive@henkel.com

Emergency Telephone for Chemical Accidents: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture
Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Gases under pressure	Compressed gas	
Flammable liquids	Category 1	
Serious eye irritation	Category 2A	
Target Organ Systemic Toxicant - Single exposure	Category 3	Central nervous system

Hazard pictogram:



Signal word: Danger

Hazard statement(s):	H224 Extremely flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.
Precautionary Statement(s):	
Prevention:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing mist/vapours. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+P403 Protect from sunlight. Store in a well-ventilated place.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

Dangerous Goods information:

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
acetone	67-64-1	20- < 30 %
butane	106-97-8	10- < 30 %
Butanone	78-93-3	10- < 20 %
ethyl formate	109-94-4	< 10 %
1,3-Dioxolane	646-06-0	1- < 3 %
non hazardous ingredients~		1- <= 10 %

Section 4. First aid measures

Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.
Skin:	Remove contaminated clothing and footwear. Wash with soap and water. Seek medical advice. Wash clothing before reuse.

Eyes:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Seek medical advice.
First Aid facilities:	Eye wash Normal washroom facilities
Medical attention and special treatment:	Treat symptomatically and supportively.

Section 5. Fire fighting measures

Suitable extinguishing media:	Foam Carbon dioxide. Dry chemical.
Decomposition products in case of fire:	Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide Carbon dioxide.
Particular danger in case of fire:	WARNING FLAMMABLE! Contents under pressure. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Special protective equipment for fire-fighters:	Use water spray to keep fire exposed containers cool and disperse vapors. Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Additional fire fighting advice:	In case of fire, keep containers cool with water spray. Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions:	Avoid contact with skin and eyes. Avoid inhalation of vapor, fumes, dust and/or mist from the spilled material.
Environmental precautions:	Do not allow to enter in surface / ground water.
Clean-up methods:	Remove the absorbed material, and place in an appropriate chemical waste container for disposal. Ventilate area.

Section 7. Handling and storage

Precautions for safe handling:	Avoid breathing vapors or mists of this product. Avoid contact with eyes, skin and clothing. Keep away from heat, spark and flame. Vapors will accumulate readily and may ignite explosively. Ensure adequate ventilation.
Conditions for safe storage:	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F).

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m ³)	Peak Limit. (ppm)	Peak Limit. (mg/m ³)	STEL (ppm)	STEL (mg/m ³)
ACETONE 67-64-1		500	1,185				
ACETONE 67-64-1						1,000	2,375
Butane 106-97-8		800	1,900				
METHYL ETHYL KETONE (MEK) 78-93-3						300	890
METHYL ETHYL KETONE (MEK) 78-93-3		150	445				
ETHYL FORMATE 109-94-4		100	303				

Engineering controls:

Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.

Eye protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Chemical resistant, impermeable gloves.
Suitable protective gloves.
Wear suitable protective clothing.
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
Butyl rubber gloves.

Respiratory protection:

If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance:	White Aerosol
Odor:	Solvent
pH:	Not applicable, Product is non-soluble (in water).6 - 8 Not applicable
Melting point / freezing point:	Not applicable, Product is a liquid-95 °C (-139 °F)
Specific gravity:	1.2
Boiling point:	< -42 °C (< -43.6 °F)56 °C (132.8 °F)
Flash point:	< -104 °C (< -155.2 °F) Solvent Mixtures
Evaporation rate:	14.4
Flammability (solid, gas):	Extremely flammable
Lower explosive limit:	1.5 %(V)2.2 %(V)
Upper explosive limit:	8.5 %(V)13 %(V)
Vapor pressure:	961 mbar (no method / method unknown; 55 °C (131 °F)None; 20 °C (68 °F); 20 °C (68 °F); 50 °C (122 °F))
Vapor density:	> 1 2.0
Density:	0.8 g/cm ³ 0.8 g/cm ³

Auto ignition: 465 °C
Decomposition temperature:

Section 10. Stability and reactivity

Stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Keep away from heat, spark and flame.
Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F).

Incompatible materials: Oxidizing agents.

Hazardous decomposition products: Thermal decomposition can lead to release of irritating gases and vapors.
carbon monoxide
carbon dioxide

Hazardous polymerization: Will not occur.

Section 11. Toxicological information

Health Effects:

Ingestion: Not expected under normal conditions of use.

Skin: Repeated exposure may cause skin dryness or cracking.
Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes: Causes serious eye irritation.
Symptoms may include severe irritation, pain, tearing, blurred vision.

Inhalation: May cause irritation to nose and throat.
Vapours may cause drowsiness and dizziness.
Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
acetone 67-64-1	LD50 LC50 LD50	5,800 mg/kg 76 mg/l > 15,688 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	not specified not specified Draize Test
butane 106-97-8	LC50	274200 ppm	inhalation	4 h	rat	not specified
Butanone 78-93-3	LD50 LC50 LD50	2,193 mg/kg 34.5 mg/l > 6,400 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 423 (Acute Oral toxicity) not specified not specified
ethyl formate 109-94-4	LD50	1,850 mg/kg	oral		rat	not specified
1,3-Dioxolane 646-06-0	LD50 LC50 LD50	> 2,000 mg/kg 68.4 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity) not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	not irritating		guinea pig	not specified
Butanone 78-93-3	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,3-Dioxolane 646-06-0	not irritating	24 h	rabbit	not specified
1,3-Dioxolane 646-06-0	not irritating		Human, EpiSkin™ (SM), Reconstructe d Human Epidermis (RHE)	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Butanone 78-93-3	irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,3-Dioxolane 646-06-0	Category 1 (irreversible effects on the eye)		Bovine, cornea, in vitro test	OECD Guideline 437 (BCOP)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
acetone 67-64-1	not sensitising	Guinea pig maximisat ion test	guinea pig	not specified
Butanone 78-93-3	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
acetone 67-64-1	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
acetone 67-64-1	negative	oral: drinking water		mouse	not specified
butane 106-97-8	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
butane 106-97-8	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Butanone 78-93-3	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without not applicable with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butanone 78-93-3	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
acetone 67-64-1	NOAEL=900 mg/kg	oral: drinking water	13 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
butane 106-97-8		inhalation: gas	28 d6 h/d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butanone 78-93-3	NOAEL=2500 ppm	inhalation	90 days6 hours/day, 5 days/week	rat	not specified
Butanone 78-93-3	LOAEL=5000 ppm	inhalation	90 days6 hours/day, 5 days/week	rat	not specified

Section 12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Ecotoxicity:

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
acetone 67-64-1	LC50	8,120 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
acetone 67-64-1	EC50	8,800 mg/l	Daphnia	48 h	Daphnia pulex	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
acetone 67-64-1	NOEC	530 mg/l	Algae	8 d	Microcystis aeruginosa	DIN 38412-09
acetone 67-64-1	EC10	1,000 mg/l	Bacteria	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
butane 106-97-8	LC50	27.98 mg/l	Fish	96 h		QSAR (Quantitative Structure Activity Relationship)
butane 106-97-8	EC50	14.22 mg/l	Daphnia	48 h		QSAR (Quantitative Structure Activity Relationship)
butane 106-97-8	EC50	7.71 mg/l	Algae	96 h		QSAR (Quantitative Structure Activity Relationship)
Butanone 78-93-3	LC50	3,220 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butanone 78-93-3	EC50	5,091 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butanone 78-93-3	EC50	1,240 mg/l	Algae	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butanone 78-93-3	EC10	1,010 mg/l	Algae	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butanone 78-93-3	EC50	1,150 mg/l	Bacteria	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)
ethyl formate 109-94-4	EC50	120 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,3-Dioxolane 646-06-0	LC50	> 95.4 mg/l	Fish	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,3-Dioxolane 646-06-0	EC50	> 772 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,3-Dioxolane 646-06-0	NOEC	877 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,3-Dioxolane 646-06-0	EC50	> 877 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,3-Dioxolane 646-06-0	EC50	> 100 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
acetone 67-64-1	readily biodegradable	aerobic	81 - 92 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
butane 106-97-8	readily biodegradable	aerobic	> 60 %	OECD 301 A - F
Butanone 78-93-3	readily biodegradable	aerobic	98 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
ethyl formate 109-94-4	readily biodegradable		77.48 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,3-Dioxolane 646-06-0	not readily biodegradable.	aerobic	3.7 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
acetone 67-64-1	-0.24					OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)
butane 106-97-8	2.31				20 °C	other (measured)
Butanone 78-93-3	0.3				40 °C	OECD Guideline 117 (Partition Coefficient (n- octanol / water), HPLC Method)
ethyl formate 109-94-4	0.23					not specified
1,3-Dioxolane 646-06-0	-0.35				20 °C	QSAR (Quantitative Structure Activity Relationship)

Section 13. Disposal considerations**Waste disposal of product:**

Dispose of according to regulations.
Contribution of this product to waste is very insignificant in comparison to article in
which it is used

Disposal for uncleaned package:

Completely empty pressurized gas containers (including propellant gas).
Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information:	Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).
UN no.:	1950
Proper shipping name:	AEROSOLS
Class or division:	2.1
Packing group:	
Emergency Information:	Refer to the Australian and New Zealand Emergency Response Guidebook

Marine transport IMDG:

UN no.:	1950
Proper shipping name:	AEROSOLS
Class or division:	2.1
Packing group:	
EmS:	F-D ,S-U
Seawater pollutant:	-

Air transport IATA:

UN no.:	1950
Proper shipping name:	Aerosols, flammable
Class or division:	2.1
Packing group:	
Packing instructions (passenger)	203
Packing instructions (cargo)	203

Section 15. Regulatory information

SUSMP Poisons Schedule	5
------------------------	---

Section 16. Other information

Abbreviations/acronyms:	ADGC - Australian Dangerous Goods Code IMDG: International Maritime Dangerous Goods code IATA-DGR: International Air Transport Association – Dangerous Goods Regulations STEL - Short term exposure limit TWA - Time weighted average AIIC - Australian Inventory of Industrial Chemicals (AIIC) AICIS - Australian Industrial Chemicals Introduction Scheme
Reason for issue:	Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Date of previous issue:

27.05.2021

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.